

4.2 Schedule of Dimensional Regulations

4.2.1 Area Requirements

	MINIMUM LOT AREA	MINIMUM LOT FRONTAGE	MINIMUM LOT AREA PER DWELLING UNIT	MAXIMUM FLOOR AREA RATIO	MAXIMUM LOT COVERAGE	MINIMUM OPEN SPACE
DISTRICTS	SQ. FT.	FEET	SQ. FT./D.U.		% OF LOT	% OF LOT
SR-A	25,000	125	--	--	20%	50%
SR-B	12,000	90	--	--	25%	50%
SR-C	9,000	75	--	--	25%	50%
SR-D	25,000	125	--	--	20%	50%
GR	5,000	50	3,500	--	30%	40%
AH	85,000	100	1,200	--	30%	40%
LB I	--	20	--	1.25	--	--
LB II	--	20	--	1.05	35%	--
LB III	--	20	--	1.05	35%	--
GB	--	20	--	--	--	--
PL	--	--	--	--	--	--

- 1) In the GR District, a minimum lot area of 7,000 square feet and a minimum lot frontage of 70 feet shall exist for a two-family dwelling.
- 2) In the GR District, the Planning Board may grant a Special Permit to modify the minimum lot area per dwelling unit and/or the minimum lot frontage requirements, pursuant to Sections 6D and 7.4 of the Zoning By-Law, provided that the lot size and frontage of the lot on which the two-family dwelling will be constructed has a minimum lot size of 5,000 square feet and a minimum lot frontage of 50 feet.
- 3) In an LBI District, a floor area ratio up to a maximum of 1.5 may be allowed by Special Permit from the Board of Appeals (see §4.4).

4.2 Schedule of Dimensional Regulations

4.2.2 Linear Requirements for Residential Districts

RESIDENTIAL DISTRICTS	MINIMUM SETBACK DIMENSIONS FEET			MAXIMUM BUILDING HEIGHT	
	Front	Side	Rear	Feet	Stories
SR-A and SR-D					
➤ Dwelling	30	15	40	36	2½
➤ Other	30	15	25	36	2½
SR-B and SR-C					
➤ Dwelling	25	10	30	36	2½
➤ Other	25	10	25	36	2½
GR					
➤ Dwelling	20	10	20	33	2½
➤ Other	20	10	12	33	2½
AH	30	30	30	60	--

A. Setbacks

- Ornamental features, such as belt courses, chimneys, eaves, gutters, sills, pilasters, or lintels, may project up to two feet into the setback.
- No building need be set back more than 30% of the depth of the lot in a Single Residence A or D District, 25% of the lot depth in a Single Residence B or C District, nor more than the average of the setbacks of the buildings on the lots contiguous thereto on either side, a vacant lot, a lot occupied by a building set back more than the required minimum, or an intersecting street being counted as though occupied by a building set back at that minimum. However, in no case shall the setback be less than 15 feet in Single Residence Districts.
- Notwithstanding the front setback requirement listed in Section 4.2.2, the front setback for the GR District shall not exceed the average of the front setbacks of the buildings on the lots contiguous thereto on either side. A vacant lot, a lot occupied by a building set back more than the required minimum, or an intersecting street shall be counted as though occupied by a building set back at that minimum.
- On lots having depth of less than 100 feet, dwelling setback from the rear lot line shall equal not less than 40% of lot depth in the Single Residence A and D Districts, not less than 30% of lot depth in Single Residence B and C Districts, and not less than 20% of lot depth in General Residence Districts; but in no event shall the rear setback equal less than 25 feet in Single Residence Districts or less than 16 feet in General Residence Districts.
- In the SR Districts, the Board of Appeals may grant a Special Permit reducing the rear setback requirement of corner lots and other unusually configured lots to not less than the side requirement, taking into consideration the configuration of the lot, and the effect upon the neighboring property.

6. In the GR Districts, on lots having depth of greater than 100 feet, dwelling setback from the rear lot line shall equal 20% of the lot depth.
7. For structures other than dwellings, on lots having depth of less than 100 feet, principal building setback from the rear lot line shall equal not less than 25% of lot depth in Single Residence Districts or 15% of lot depth in General Residence Districts. For accessory buildings, see Section 4.3.5.

B. Height

1. Chimneys, towers and other projections not used for human occupation may exceed the height limitations herein provided that, except for single vertical freestanding tubular antennae; any such projection above the building exceeding 10 feet or 20% of the building height, whichever is greater, shall be allowed by Special Permit only.
2. In the SR Districts, greater height is permitted provided the building setback from each street and lot line exceeds otherwise applicable requirements by 10 feet plus one foot for each foot of excess height, but in no case shall building height exceed 60 feet or 4 stories in height.

4.2.3 Linear Requirements for Commercial Districts

COMMERCIAL DISTRICTS	MINIMUM SETBACK DIMENSIONS FEET			MAXIMUM BUILDING HEIGHT	
	Front	Side	Rear	Feet	Stories
LB I	5	6 or none	6 or none	28	2
LB II	10	0	20	32	2
LB III	10	0	20	28	2
GB	5	6 or none	6 or none	36	--
PL	--	--	--	--	--

A. Setbacks

1. Ornamental features, such as belt courses, chimneys, eaves, gutters, sills, pilasters, or lintels, may project up to two feet into the setback.
2. In the LB III Districts, for structures originally built as residences and not adjacent to Residential District, the lesser of the side setback existing as of May 5, 2003, or 10 feet.
3. Adjacent to Residential District, the side and/or rear setback shall be no less than building height or 20 feet, whichever is greater.

B. Height

1. Chimneys, towers and other projections not used for human occupation may exceed the height limitations herein provided that, except for single vertical freestanding tubular antennae; any such projection above the building exceeding 10 feet or 20% of the building height, whichever is greater, shall be allowed by Special Permit only.
2. No more than two stories wholly or partially above grade.
3. In LBI Districts, a maximum building height of up to 32 feet and 3 stories may be allowed by Special Permit from the Board of Appeals, as provided in Section 4.4.

TRUE COPY ATTEST: _____

Ellen O'Brien Cushman, Town Clerk
Belmont, MA